

浙大三色

Email:sensing@sensingm.com

Tel:+86 571 85021543 Fax:+86 571 87977635

ROLED

灯具名称: 投光灯

灯具描述: F1223A1-9-36DC-RC-Y(30-CL-9RGBWN-AJ, CT)

报告编号:

电压(V): 35.6000

测试编号: 20210301011

电流(A): 0.3880

光源规格型号: CL

功率(W): 13.8000

每个光源光通量(lm)

功率因数: 1.0350

光源数量: 9

镇流器型号:

发光面长度(mm): 110

发光面宽度(mm): 110

测试模式: C

发光面高度(mm): 0

光度结果

灯具光通量(lm): 546.55

灯具效能(lm/w): 39.61

中心光强(cd): 1118.758

最大光强(cd): 1137.942

最大光强角度: $C=240.0 \gamma=2.0$

半峰边角(50%Imax): [C0/180]Total=31.2

[C90/270]Total=30.9



光束扩散角(10%Imax): [C0/180]Total=70.5

[C90/270]Total=71.6

测试设备: GMS1800
环境温度(°C): 25.0

测试日期: 2021/3/1
环境湿度(%): 60.0%


测试人员: anpeilou
测试距离(m): 8.76



C240(Max): —
C0/C180: —
C90/C270: —


ROLED 投光灯

照度距离图表



Max , Ave C240面光束角32.22

ROLED 投光灯
平面等照度曲线



(10%Emax) 12.55	——
(20%Emax) 25.09989	——
(30%Emax) 37.64989	——
(40%Emax) 50.19989	——
(50%Emax) 62.74989	——
(60%Emax) 75.29977	——
(70%Emax) 87.84978	——
(80%Emax) 100.3998	——
(90%Emax) 112.95	——

测试设备: GMS1800
环境温度(°C): 25.0

测试日期: 2021/3/1
环境湿度(%): 60.0%

测试人员: anpeilou
测试距离(m): 8.76

ROLED 投光灯

灯具的亮度限制曲线(灯具无发光侧边)

附页 第 5页 共8页

亮度值表


γ	45	50	55	60	65	70	75	80	85
C0	0	5278	0	3310	0	2244	0	1570	0
C45	0	0	0	0	0	0	0	0	0
C90	0	4154	0	2778	0	1910	0	1242	0

L横(65)	L纵(65)	L45(65)	L横(75)	L纵(75)	L45(75)	L横(85)	L纵(85)	L45(85)
331070	355252	0	293330	314011	0	97724	100489	0

眩光等级表

眩光等级	质量等级	使用照度(lx)							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h

亮度限制曲线



测试设备: GMS1800
环境温度(°C): 25.0

测试日期: 2021/3/1
环境湿度(%): 60.0%

测试人员: anpeilou
测试距离(m): 8.76

参照UGR的照射评估											
天花板反射率	70	70	50	50	30	70	70	50	50	30	
墙壁反射率	50	30	50	30	30	50	30	50	30	30	
地板反射率	20	20	20	20	20	20	20	20	20	20	
空间尺寸	Viewed crosswise					Viewed endwise					
X	Y										
2H	2H	15.26	16.38	15.63	16.69	17.01	14.78	15.90	15.15	16.21	16.53
	3H	16.10	17.09	16.48	17.42	17.79	15.64	16.63	16.03	16.97	17.33
	4H	16.36	17.28	16.77	17.63	18.02	15.92	16.83	16.32	17.19	17.57
	6H	16.52	17.36	16.93	17.73	18.13	16.08	16.92	16.49	17.29	17.69
	8H	16.54	17.33	16.97	17.72	18.13	16.10	16.90	16.54	17.29	17.70
	12H	16.56	17.31	16.99	17.70	18.13	16.13	16.89	16.56	17.27	17.70
4H	2H	15.46	16.38	15.87	16.73	17.12	15.05	15.97	15.45	16.32	16.71
	3H	16.48	17.23	16.90	17.64	18.04	16.09	16.83	16.50	17.24	17.65
	4H	16.83	17.50	17.27	17.92	18.37	16.45	17.12	16.89	17.54	17.98
	6H	17.02	17.59	17.49	18.04	18.51	16.65	17.22	17.11	17.67	18.14
	8H	17.06	17.59	17.53	18.04	18.52	16.70	17.23	17.17	17.68	18.15
	12H	17.09	17.55	17.58	18.04	18.51	16.73	17.19	17.22	17.68	18.16
8H	4H	16.88	17.42	17.36	17.86	18.34	16.53	17.06	17.00	17.51	17.99
	6H	17.14	17.57	17.65	18.07	18.56	16.81	17.23	17.31	17.74	18.22
	8H	17.23	17.61	17.76	18.13	18.62	16.90	17.28	17.43	17.80	18.29
	12H	17.85	18.18	18.37	18.68	19.25	17.51	17.84	18.03	18.34	18.92
12H	4H	16.85	17.32	17.34	17.80	18.28	16.50	16.97	16.99	17.45	17.93
	6H	17.51	17.51	17.66	17.98	18.53	17.18	17.18	17.33	17.65	18.20
	8H	17.24	17.57	17.76	18.07	18.65	16.92	17.25	17.44	17.75	18.33
对应照射距离，改变观察者位置S											
S = 1.0H	0.8/-1.2					1.1/-1.2					
S = 1.5H	1.7/-1.9					2.3/-1.9					
S = 2.0H	3.8/-2.3					4.4/-2.3					
标准表格	BK2					BK2					
更正系数	-3.6					-2.7					

ROLED 投光灯

光强数据表(cd)

附页 第7页 共8页

C/γ(°)	0.0	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0
0.0	1118.76	1109.55	1075.09	1015.70	934.66	844.19	750.57	650.12	557.88
30.0	1132.26	1098.65	1043.17	964.36	870.05	769.83	673.22	575.84	487.74
60.0	1126.74	1084.38	1017.08	927.91	829.07	730.16	627.25	537.47	452.06
90.0	1127.97	1085.53	1022.30	934.66	838.28	733.53	630.09	537.24	449.99
120.0	1121.83	1081.23	1014.85	927.07	833.68	730.62	632.70	537.62	452.06
150.0	1121.44	1092.90	1037.65	960.83	868.59	774.82	673.60	581.21	492.73
180.0	1118.76	1098.42	1054.68	985.16	899.52	803.44	707.14	609.83	524.19
210.0	1132.26	1135.64	1110.24	1057.29	984.85	901.44	802.83	704.22	614.28
240.0	1126.74	1137.94	1119.99	1076.55	1007.56	924.53	830.45	736.45	642.91
270.0	1127.97	1135.64	1114.15	1068.03	998.20	912.26	820.32	723.10	629.02
300.0	1121.83	1132.34	1113.08	1067.11	1001.73	919.70	830.76	727.86	639.99
330.0	1121.44	1121.44	1092.97	1041.64	968.66	886.24	783.57	691.94	599.47
360.0	1118.76	1109.55	1075.09	1015.70	934.66	844.19	750.57	650.12	557.88
C/γ(°)	18.0	20.0	22.0	24.0	26.0	28.0	30.0	32.0	34.0
0.0	477.46	401.26	341.33	284.24	241.03	204.74	175.19	148.49	127.38
30.0	413.62	345.70	289.15	242.11	204.74	172.51	147.11	124.93	106.51
60.0	376.40	313.40	263.52	219.47	183.71	155.85	131.76	112.19	95.92
90.0	373.79	309.10	258.07	214.02	180.26	151.56	128.23	110.04	93.62
120.0	376.55	313.70	263.59	219.47	185.32	155.93	131.99	112.11	96.46
150.0	414.08	349.23	292.14	244.41	204.66	173.50	146.65	124.39	106.82
180.0	442.16	372.10	312.09	263.98	222.39	187.78	160.30	136.52	117.64
210.0	524.27	450.37	383.07	324.29	276.56	235.66	202.05	173.43	149.95
240.0	554.66	478.00	410.16	353.91	300.50	260.91	224.76	194.91	168.82
270.0	539.54	466.64	400.19	342.56	298.05	258.38	223.54	194.84	170.43
300.0	552.74	476.77	409.70	351.38	301.50	261.98	226.07	195.14	170.28
330.0	511.84	440.70	375.55	321.22	274.03	234.28	199.82	173.12	149.02
360.0	477.46	401.26	341.33	284.24	241.03	204.74	175.19	148.49	127.38
C/γ(°)	36.0	38.0	40.0	42.0	44.0	46.0	48.0	50.0	52.0
0.0	110.12	94.31	81.73	70.68	61.70	53.95	46.96	41.05	35.76
30.0	91.39	79.27	68.45	59.47	52.18	45.51	39.83	35.07	30.54
60.0	83.11	71.75	62.62	54.64	47.81	41.90	36.68	32.38	28.47
90.0	81.27	70.37	61.70	53.79	47.12	41.75	36.76	32.31	28.24
120.0	82.80	72.13	62.46	54.48	47.58	41.67	36.76	32.15	28.09
150.0	91.55	78.81	68.07	59.47	51.72	45.35	39.75	34.69	30.31
180.0	100.07	86.87	75.13	65.07	56.86	49.65	43.43	37.45	32.61
210.0	128.15	110.58	95.15	82.34	71.44	61.85	53.64	46.50	40.75
240.0	145.65	126.31	109.43	94.31	81.34	70.98	61.31	52.95	45.97
270.0	147.41	129.00	112.04	96.69	84.49	73.28	63.31	54.94	47.73
300.0	147.18	126.92	110.04	95.77	82.65	71.67	62.31	53.79	46.89
330.0	127.54	110.96	95.92	83.11	71.60	62.54	54.10	47.19	40.98
360.0	110.12	94.31	81.73	70.68	61.70	53.95	46.96	41.05	35.76
C/γ(°)	54.0	56.0	58.0	60.0	62.0	64.0	66.0	68.0	70.0
0.0	30.93	26.70	23.25	20.03	17.19	14.89	12.66	10.82	9.29
30.0	26.78	23.25	20.26	17.57	15.27	13.12	11.28	9.67	8.36
60.0	25.02	21.87	19.03	16.58	14.50	12.74	11.05	9.59	8.21
90.0	25.02	21.87	19.26	16.81	14.50	12.58	10.90	9.29	7.90
120.0	24.79	21.64	18.80	16.35	14.20	12.35	10.82	9.13	7.75
150.0	26.63	23.02	19.95	17.27	14.89	12.74	11.05	9.52	8.13
180.0	28.16	24.40	21.03	17.96	15.50	13.28	11.36	9.67	8.29
210.0	34.99	30.16	25.86	21.95	18.72	15.81	13.43	11.28	9.44
240.0	39.52	33.69	28.93	24.63	20.80	17.65	14.96	12.58	10.59
270.0	40.98	35.22	30.31	25.48	21.49	17.96	15.04	12.51	10.51
300.0	39.83	34.53	29.62	25.32	21.33	18.03	15.27	12.97	10.90
330.0	35.30	30.70	26.17	22.41	19.11	16.35	13.74	11.59	9.67
360.0	30.93	26.70	23.25	20.03	17.19	14.89	12.66	10.82	9.29

ROLED 投光灯

光强数据表(cd)

附页 第 8页 共8页

C/γ(°)	72.0	74.0	76.0	78.0	80.0	82.0	84.0	86.0	88.0
0.0	7.75	6.52	5.22	4.22	3.30	2.46	1.61	0.69	0.23
30.0	7.14	5.99	4.99	3.91	2.76	1.92	1.07	0.31	0.08
60.0	6.83	5.45	4.45	3.53	2.69	1.76	0.84	0.31	0.08
90.0	6.91	5.76	4.60	3.61	2.61	1.76	0.92	0.23	0.00
120.0	6.52	5.29	4.30	3.38	2.53	1.61	0.92	0.23	0.00
150.0	6.91	5.83	4.76	3.76	2.69	1.69	1.00	0.31	0.08
180.0	6.91	5.60	4.60	3.61	2.76	2.00	1.15	0.38	0.15
210.0	7.98	6.68	5.53	4.37	3.38	2.38	1.53	0.84	0.23
240.0	8.90	7.21	5.68	4.45	3.53	2.69	1.84	0.92	0.31
270.0	8.67	7.37	6.06	4.83	3.68	2.61	1.69	0.84	0.23
300.0	8.98	7.44	5.91	4.60	3.68	2.69	1.84	1.00	0.31
330.0	8.06	6.83	5.76	4.53	3.45	2.53	1.69	0.84	0.23
360.0	7.75	6.52	5.22	4.22	3.30	2.46	1.61	0.69	0.23

C/γ(°)	90.0
0.0	0.00
30.0	0.00
60.0	0.00
90.0	0.00
120.0	0.00
150.0	0.00
180.0	0.00
210.0	0.08
240.0	0.08
270.0	0.08
300.0	0.08
330.0	0.00
360.0	0.00